

C1071Y-C6

10.4英寸电容屏工业平板



Product characteristics

- 10.4-inch LCD, 800*600, capacitive touch screen
- Integrated Intel®i5-4310U/2.00GHz dual-core quad-thread processor
- 1*SODIMM DDR3L 1600MHz memory, up to 8GB
- 1*HD OUTPUT
- 2*Intel I210AT Gigabit network adapter
- 6*RS232 serial port, COM1~2 RS232 DB9 serial port, COM2 supports RS485/422, COM3~6 RS232/485/422 on the 2*15P Phoenix terminal
- 2*15Pin Phoenix terminal, four in four out GPIO, switch, 5V, GND
- 2*USB3.0, 2*USB2.0
- 9~36V wide voltage input

Model number	C1071Y-C6 V1.0(4310U)	
chassis	Material/Structure	Aluminum alloy material, fanless cooling structure
	colour	silver
	Dimensions (length, width and height)	L272*W214*H62mm
	Weight (bare weight)	2.63 KG
	Install	Support VESA/ embedded panel installation
LCD screen	type	10.4 inch LCD
	Resolution	800 * 600
	luminance	350 cd/m2
Touch screen	type	Capacitive screen, 10 touch
	Light transmittance	More than 85%
Main board	CPU	Integrated Intel®i5-4310U/2.00GHz dual-core quad-thread processor, TDP 15W
	reveal	Integrated Intel® HD Graphics 4400
	Internal memory	1 * DDR3L SODIMM slot, supporting 1600 MHZ memory and a maximum of 8GB memory
IO interface	POWER	1* Power button, 1* one key restore (and reset key to choose one), 1*ACLOSS (power on DIP switch)
	LED	1* Power indicator, 1* hard disk indicator
	Display interface	1 * HD OUTPUT1.4
	LAN	2*Intel I210AT Gigabit network adapter, supporting network wake up and PXE functions
	USB	2 * USB3.0, 2 x USB2.0
	COM	6*RS232 serial port, COM1~2 RS232 DB9 serial port, of which COM2 supports RS485/422, COM3~6 RS232/485/422 On the 2*15P Phoenix terminal, COM1-2 supports 9pin live function
	Phoenix terminal	2*15Pin(4 in 4 out GPIO, switching signal, COM3~COM6 (RS232/RS485/422), 5V VCC and GND)
	Dip switch	10-bit dip switch, COM2~6 RS232/485/422 switch
	Audio frequency	1*Line out, 1*MIC
	Power source	1*DC aviation interface or 1*2Pin Phoenix terminal, support 9V~36V wide voltage input




工业平板

所有产品规格变更, 均不另行通知

store	SATA	1 x 2.5-inch hard disk
	MSATA	1*MSATA
extend	M.2	1*M.2/WiFi, supports Key-E, 2230, WiFi module
		1*M.2/5G, supports Key-B, 2242/52, 5G modules
System support	Windows	Windows 7
	Linux	Ubuntu
	Watch Dog	Support hardware reset function (256 level, 0~255 seconds)
Power demand	Power supply type	External power adapter
	Voltage input	9V~36V wide voltage
	Power output	36W~90W (depending on the equipment)
environment	Operating temperature	-10°C to 50°C
	Storage temperature	-20°C to 70°C
	Relative humidity	5%-95% relative humidity, no condensation
	Working vibration	0.5g rms/5-500HZ/random/operating

C1071Y-C6尺寸图




前面板视图



后面板视图



侧面 I/O 视图



底部I/O视图

订货信息

No.	Model	CPU	Memory	Motherboard	IO Board	GPIO	LAN	COM	HD OUTPUT	USB	power
1	C1071Y-C6 V1.0(J1900)	J1900/2.0G	1*SODDDR3L	C19	P1071-C6/P1071-LED	4 in and 4 out	2	6	1	4	9~36V
2	C1071Y-C6 V1.0(4310U)	I5-4310U/2.0G	1*SODDDR3L	C43	P1071-C6/P1071-LED	4 in and 4 out	2	6	1	4	9~36V
3	C1071Y-C6 V1.0(4600U)	I7-4600U/2.1G	1*SODDDR3L	C43	P1071-C6/P1071-LED	4 in and 4 out	2	6	1	4	9~36V

NOTE: 1、不支持亮度调节，默认最大亮度，

2、一键还原与复位键二选一，默认一键还原，部分CPU不支持一键还原，具体联系FAE，需要默认复位键，需更改硬件

